

Order Code
(further options on request)

Uniflux 1/4"

S

V

S

1-10 l/min

AI

OC

IR

LS

Series name

Uniflux 1/4"

Models

C Compact (133mm)

S Standard (210mm)

L Long (250mm)

Variant

A Angled (without valve / horizontal connection)

S Straight (without valve / vertical connection)

V Integral Valved (with valve / horizontal connection)

Material

B Nickel Plated **B** Brass

S Stainless Steel

Measuring range (depending on medium)

5-100 cm³/min, 20-250 cm³/min, 60-600 cm³/min, 50-750 cm³/min,
0,1-1,2 l/min, 0,2-2,0 l/min, 0,3-3,0 l/min, 0,6-5,0 l/min,
1-10 l/min, 1-13 l/min, 2-26 l/min, 4-50 l/min, 10-100 l/min

Medium (model dependent)

N:3H, Ar, C4H10, He, CO₂, CO, Air (**AI**), CH₄, C₃H₈, O₂, N₂ H₂O, H₂

Oxygen purified (Oil and grease-free)

... without cleaning

OC oxygen-cleaned

Infrared alarm

... no infrared alarm installed on the device

IR 1 infrared alarm installed on the device

2IR 2 infrared alarms installed on the device

Laboratory stand

... no laboratory stand installed on the device

LS with laboratory stand installed on the device

